



7' Wide Cargo Specifications



7' WIDE SINGLE AXLE

SPECIFICATIONS:

	I 710 SAFS	I 712 SAFS	I 714 SAFS
Overall			
Length	13' 11"	15' 11"	17' 11"
Width	8' 6"	8' 6"	8' 6"
Height	7' 11"	7' 11"	7' 11"
Interior			
Length	10' 4"	12' 4"	14' 4"
Width	6' 8"	6' 8"	6' 8"
Height	6' 4"	6' 4"	6' 4"
Side wall			
Height	5' 10"	5' 10"	5' 10"
Distance between w/w	6' 8"	6' 8"	6' 8"
Rear Door	Double	Double	Double
Width	6' 5"	6' 5"	6' 5"
Height	5' 10"	5' 10"	5' 10"
Hitch			
Weight	165 lbs.	180 lbs.	195 lbs.
Height	14"	14"	14"
Ball Size	2"	2"	2"
Platform height	17"	17"	17"
G.V.W.R.	3,500 lbs.	3,500 lbs.	3,500 lbs.
Curb Weight	1,560 lbs.	1,710 lbs.	1,860 lbs.
Payload Capacity	1,940 lbs.	1,790 lbs.	1,640 lbs.
Axles (single)	3,500 lbs.	3,500 lbs.	3,500 lbs.
Brakes	Electric	Electric	Electric
Tires	ST205 75/r15 (c)	ST205 75/r15 (c)	ST205 75/r15 (c)
Wheels	5 on 4 1/2	5 on 4 1/2	5 on 4 1/2
Frame	3" tube	3" tube	3" tube
Floor (24" o/c)	3/4" plywood	3/4" plywood	3/4" plywood
Side Walls (16" o/c)	3/8" plywood	3/8" plywood	3/8" plywood



7' Wide Single Axle

Work, work, work...that's what this over-achiever was designed for. But don't think it's not just as versatile when it comes to recreation. Available with a wide track option that's perfect for hauling long and bulky items.

7' WIDE TANDEM AXLE

SPECIFICATIONS:

	I 712 TA2	I 714 TA2	I 716 TA2	I 718 TA2
Overall				
Length	15' 8"	17' 8"	19' 8"	21' 8"
Width	7' 10"	7' 10"	7' 10"	7' 10"
Height	8' 5"	8' 5"	8' 5"	8' 5"
Interior				
Length	12' 5"	14' 5"	16' 5"	18' 5"
Width	6' 8"	6' 8"	6' 8"	6' 8"
Height	6' 7"	6' 7"	6' 7"	6' 7"
Sidewall				
Height	6'	6'	6'	6'
Distance between w/w	6' (*see note)	6' (*see note)	6' (*see note)	6' (*see note)
Rear Door	Double	Double	Double	Double
Width	6' 5"	6' 5"	6' 5"	6' 5"
Height	6'	6'	6'	6'
Hitch				
Weight	220 lbs.	230 lbs.	250 lbs.	270 lbs.
Height	17"	17"	17"	17"
Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"
Platform height	20"	20"	20"	20"
G.V.W.R.	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
Curb Weight	2,195 lbs.	2,270 lbs.	2,445 lbs.	2,620 lbs.
Payload Capacity	4,905 lbs.	4,730 lbs.	4,555 lbs.	4,380 lbs.
Axles (tandem)	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
Brakes	Electric	Electric	Electric	Electric
Tires	ST205 75/r15 (c)	ST205 75/r15 (c)	ST205 75/r15 (c)	ST205 75/r15 (c)
Wheels	5 on 4 1/2	5 on 4 1/2	5 on 4 1/2	5 on 4 1/2
Frame	8" I-beam	8" I-beam	8" I-beam	8" I-beam
Floor (24" o/c)	3/4" plywood	3/4" plywood	3/4" plywood	3/4" plywood
Sidewalls (16" o/c)	3/8" plywood	3/8" plywood	3/8" plywood	3/8" plywood

*Note: optional 92" hub face axles (no interior fender wells) allows for flush walls

STANDARD FEATURES:

- Torsion Axles
- 9" Aluminum Tread Plate Fenders (Single Axle Only)
- 4" Aluminum Fenders (Tandem Axle Only)
- Electric Brakes All Hubs
- Welded Safety Chains
- E-Z Lube Hubs with Grease Caps
- Undercarriage Sealed with Asphalt-Based Undercoating
- 12-Volt Breakaway Switch with Battery & Charger
- Goodyear Marathon Radial Tires
- .030 Smooth Aluminum Exterior (Available in 11 Colors)
- E-coated & Powder-Coated White Wheels
- License Plate Holder with Built-in Light
- Double Rear Doors
- Semi-Style Camlock Door Latches
- Door Hold Backs on All Doors
- Crimped Aluminum Exterior Seams

POPULAR OPTIONS:

- Millennium Package
- Motorcycle Package (See Dealer for Details)
- Stoneguard
- RV Side Door
- Roof Vent
- Dome Light
- Spare Tire Tongue Mount
- Additional Interior Height
- Ramp Door with Spring Assist
- White Vinyl Ceiling Liner
- Rear Stabilizer Jacks
- 110-Volt Options
- Black and White Vinyl Floor
- Rear Ramp with Assist
- Insulation
- Recessed or Surface Rope Ties
- Ladder Racks
- RV-Style Tinted Windows with Screens
- Aero Flow Vents
- Many Other Options Available

For more information, see our Cargo Trailer brochure, contact your local dealer or visit us at www.interstatecargo.com

