



# 7' Wide V-Nose Specifications



## 7' WIDE V-NOSE SINGLE AXLE

### SPECIFICATIONS:

	IVC 712 SAFS	IVC 714 SAFS	IVC 716 SAFS
<b>Overall</b> Length	13' 11"	15' 11"	17' 11"
Width	8' 6"	8' 6"	8' 6"
Height	7' 11"	7' 11"	7' 11"
<b>Interior</b> Length	11' 8"	13' 8"	15' 8"
Width	6' 8"	6' 8"	6' 8"
Height	6' 4"	6' 4"	6' 4"
<b>Sidewall</b> Height	5' 10"	5' 10"	5' 10"
<b>Wedge</b> Length	23"	23"	23"
<b>Distance between w/w</b>	6' 8"	6' 8"	6' 8"
<b>Rear Door</b>	Double	Double	Double
Width	6' 5"	6' 5"	6' 5"
Height	5' 10"	5' 10"	5' 10"
<b>Hitch</b> Weight	165 lbs.	180 lbs.	195 lbs.
Height	14"	14"	14"
Ball Size	2"	2"	2"
<b>Platform height</b>	17"	17"	17"
<b>G.V.W.R.</b>	3,500 lbs.	3,500 lbs.	3,500 lbs.
<b>Curb Weight</b>	1,640 lbs.	1,710 lbs.	1,940 lbs.
<b>Payload Capacity</b>	1,860 lbs.	1,710 lbs.	1,560 lbs.
<b>Axles (single)</b>	3,500 lbs.	3,500 lbs.	3,500 lbs.
<b>Brakes</b>	Electric	Electric	Electric
<b>Tires</b>	ST205 75/r15 (c)	ST205 75/r15 (c)	ST205 75/r15 (c)
<b>Wheels</b>	5 on 4 1/2	5 on 4 1/2	5 on 4 1/2
<b>Frame</b>	3" tube	3" tube	3" tube
<b>Floor (24" o/c)</b>	3/4" plywood	3/4" plywood	3/4" plywood
<b>Sidewalls (24" o/c)</b>	3/8" plywood	3/8" plywood	3/8" plywood

## 7' WIDE V-NOSE TANDEM AXLE

### SPECIFICATIONS:

	IVC 712 TA2	IVC 714 TA2	IVC 716 TA2	IVC 718 TA2
<b>Overall</b> Length	14' 2"	16' 2"	18' 2"	20' 2"
Width	7' 10"	7' 10"	7' 10"	7' 10"
Height	8' 5"	8' 5"	8' 5"	8' 5"
<b>Interior</b> Length	11' 10"	13' 10"	15' 10"	17' 10"
Width	6' 8"	6' 8"	6' 8"	6' 8"
Height	6' 7"	6' 7"	6' 7"	6' 7"
<b>Sidewall</b> Height	6'	6'	6'	6'
<b>Wedge</b> Length	19"	19"	19"	19"
<b>Distance between w/w</b>	6'	6'	6'	6'
<b>Rear Door</b>	Double	Double	Double	Double
Width	6' 5"	6' 5"	6' 5"	6' 5"
Height	6'	6'	6'	6'
<b>Hitch</b> Weight	220 lbs.	230 lbs.	250 lbs.	270 lbs.
Height	17"	17"	17"	17"
Ball Size	2 5/16"	2 5/16"	2 5/16"	2 5/16"
<b>Platform height</b>	20"	20"	20"	20"
<b>G.V.W.R.</b>	7,000 lbs.	7,000 lbs.	7,000 lbs.	7,000 lbs.
<b>Curb Weight</b>	2,120 lbs.	2,295 lbs.	2,370 lbs.	2,545 lbs.
<b>Payload Capacity</b>	4,860 lbs.	4,705 lbs.	4,630 lbs.	4,455 lbs.
<b>Axles (tandem)</b>	3,500 lbs.	3,500 lbs.	3,500 lbs.	3,500 lbs.
<b>Brakes</b>	Electric	Electric	Electric	Electric
<b>Tires</b>	ST205 75/r15 (c)	ST205 75/r15 (c)	ST205 75/r15 (c)	ST205 75/r15 (c)
<b>Wheels</b>	5 on 4 1/2	5 on 4 1/2	5 on 4 1/2	5 on 4 1/2
<b>Frame</b>	8" I-beam	8" I-beam	8" I-beam	8" I-beam
<b>Floor (24" o/c)</b>	3/4" plywood	3/4" plywood	3/4" plywood	3/4" plywood
<b>Sidewalls (16" o/c)</b>	3/8" plywood	3/8" plywood	3/8" plywood	3/8" plywood

Note: All V-Nose trailers have a 2' front V-Nose Interior. Example: 14' trailer (12' box 2' V-Nose)



### STANDARD FEATURES:

- **Stoneguard**
- Aerodynamic Wedge Front
- Torsion Axle
- 9" Aluminum Tread Plate Fenders (Single Axle Only)
- Electric Brakes all Hubs
- Welded Safety Chains
- E-Z Lube Hubs with Grease Caps
- Undercarriage Sealed with Asphalt-Based Undercoating
- 12-Volt Breakaway Switch With Battery & Charger
- Goodyear Marathon Radial Tires
- .030 Smooth Aluminum Exterior (Available in 11 Colors)
- E-coated & Powder-Coated White Wheels
- License Plate Holder with Built-in Light
- Double Rear Doors
- Semi-Style Camlock Door Latches
- Door Hold Backs on all Doors
- 4" Aluminum Fenders (Tandem Axle Only)
- Bright Anodized Aluminum Nose
- Crimped Aluminum Exterior Seams

### POPULAR OPTIONS:

- **Millennium Package**
  - **Motorcycle Package** (See Dealer for Details)
  - RV Style Side Door
  - Roof Vent
  - Dome Light
  - Spare Tire Interior Mount
  - Additional Interior Height
  - Ramp Door with Spring Assist
  - White Vinyl Ceiling Liner
  - Rear Stabilizer Jacks
  - 110-Volt Options
  - Black and White Vinyl Floor
  - Rear Ramp with Spring Assist
  - Insulation
  - Recessed or Surface Rope Ties
  - Aero Flow Vents
  - Many Other Options Available
- Note: optional 92" hub face axles (no interior fender wells) allows for flush walls (standard on single axle)

For more information, see our Cargo Trailer brochure, contact your local dealer or visit us at [www.interstatecargo.com](http://www.interstatecargo.com)

